

Description

The 80365 mobile parts washer from Alemlube is the ideal addition to any workshop looking to keep tools and mechanical parts & components clean and free of contaminants.

Easily moved from one workshop location to another, this well designed washing bay is self contained with a lid that can be latched closed at the end of the job.

The 80365 is mounted on a pedestal at an OH&S acceptable height and features sturdy lockable wheels, storage space, interchangeable cleaning brushes, tools support rail, integrated emptying plug and simply plugs into a 240V power outlet for instant on demand operation.

Specifications

Uses	Cleaning of tools, mechanical parts and components
Pump flow	15L/min of solvent or general parts cleaning fluids
Materials	PE HD
Weight	9.0kg (empty) 10kg maximum weight in working tank
Working Tank Size	430mm x 420mm x 60mm

Operating instructions

1

Fill the Parts Washer through the cleaning tank, after having taken off the plug clog, for the product to flow in the case.

Do not move the Parts Washer during use.

2

To turn on the Parts Washer, connect the power cord into a standard 240V outlet and switch the unit on. The pump will then activate the circulation and the brush will be supplied with cleaning solution.

3

If you wish to move the Parts Washer without emptying the solution, lift it up flat, utilising the 2 notches located under the unit, on both sides of the case. The unit must be flat during transport and the plug must be well pushed in, in order to avoid any outflow.

4

In order to change or renew the cleaning solution, empty the Parts Washer by unscrewing the red plug located under the cleaning tank.

5

NSW

Do not operate the Parts Washer without cleaning solution. Damage to the pump could result.





🕭 Alemlube

🜢 Alemlube